POSEIDON® P1 PORTABLE SECTIONAL BARGES

	P1-5-20	Section	P1-5-40	Section
Length, Overall	20'-1"	6.12 m	40'-1"	12.22 m
Width, Overall	10'-1"	3.07 m	10'-1"	3.07 m
Height, Overall	5'-0"	1.52 m	5'-0"	1.52 m
Shipping Weight, Approx.	12,500 lbs	5,670 kg	23,100 lbs	10,478 kg
Draft, Unloaded	12"	0.30 m	11"	0.28 m
Draft, Full Load	30"	0.76 m	30"	0.76 m
Payload at Full Load	9.0 tons	8.2 mT	19.0 tons	17.2 mT







Standard Features:

- Baril DCC Paint System including Zinc Rich Primer Coat & Premium Abrasion-Resistant Topcoat
- Flush Mounted, Sacrificial Zinc Anodes provide added Corrosion Protection
- Internal void spaces coated with Biofloat environmentally friendly Corrosion Inhibitor
- Patented Heavy Duty Roll Form, HSLA Steel Deck Construction with 20,000 psf Concentrated Load Capacity
- The high strength to weight ratio allows two 40ft barges to be shipped per truck, saving freight costs!

Available Poseidon Accessories:

- Spud Pockets
- Spuds, 18" diameter x 1/2" wall thickness, in a wide range of lengths from 20ft to 80ft
- Double Drum Hydraulic Winch Systems
- Deck Cleats, Handrail, Safety Ladder
- Sea Bee Thruster System

U.S. Patent #8,327,789
Poseidon® Sea Bee Pusher
& deck cleat





POSEIDON® BARGE, LTD

725 East Parr Road, Berne, ÍN 46711 PH: 866-99-BARGE; FAX: 260-589-2088 WEBSITE: www.poseidonbarge.com

STOCK LOCATIONS: Berne, IN • Plain, WI • Leland, NC Cocoa, FL • Coeymans, NY • St. Louis, MO • New Orleans, LA



Hauling 2-40' x 10' x 5' sections per truck saves time and money on every project!

POSEIDON® P1 BARGES are connected with a hairpin style connector pins allowing quick & easy assembly on the job with no additional tools. The P1 Barge does not have to be turned a certain way to connect to the next barge. All side and end castings are universal.

A single pick 25 ton shackle on the top center of the barge speeds the unloading and set up process.

POSEIDON® BARGE, LTD offers competitive pricing & friendly service.

The Poseidon® P1 Portable Barge is easily transported from job to job on light weight step deck trailers.







External mount Spud Pockets can be located at any two connection points on the sides or ends of the barge.

The roll formed patented top design U.S. D0807,9320 deck is rated at 20,000 psf; four times stronger than our competition. We require the use of wood mats to protect the deck surface.

Shipping Weights

40' x 10' x	< 5'	23,089 lbs.
20' x 10' x	< 5'	12,726 lbs.
10' x 10' >	ć 5' rakes	6,368 lbs.
Spud Poo	kets	1,794 lbs.
18" x 40'	Spuds	4,667 lbs.
18" x 30'	Spuds	3,636 lbs.
18" x 20'	Spuds	2,595 lbs.
Connecto	r Pins	55 lbs.
Spud Wir	nch	4,500 lbs
Cleats		60 lbs.
Drill Space	ers	215 lbs.







POSEIDON® BARGE, LTD

725 East Parr Road, Berne, ľN 46711 PH: 866-99-BARGE; FAX: 260-589-2088 WEBSITE: www.poseidonbarge.com

STOCK LOCATIONS: Berne, IN • Plain, WI • Leland, NC Cocoa, FL • Coeymans, NY • St. Louis, MO • New Orleans, LA