

POSEIDON® P1 NARROW SECTIONAL BARGES

P1-4N-15 Section P1-4N-30 Section

	P1-4N-15 Section	P1-4N-30 Section	P1-4N-15 Section	P1-4N-30 Section
Length, Overall	15'-1"	4.60 m	30'-1"	9.17 m
Width, Overall	7'-7"	2.31 m	7'-7"	2.31 m
Height, Overall	4'-0"	1.22 m	4'-0"	1.22 m
Shipping Weight, Approx.	8,100 lbs	3,674 kg	14,700 lbs	6,668 kg
Draft, Unloaded	14"	0.30 m	13"	0.28 m
Draft, Full Load	24"	0.61 m	24"	0.61 m
Payload at Full Load	2.7 tons	2.5 mT	6.3 tons	5.7 mT



Standard Features:

- Baril DCC Paint System including Zinc Rich Primer Coat & Premium Abrasion-Resistant Topcoat
- Flush Mounted, Sacrificial Zinc Anodes provide added Corrosion Protection
- Internal Void Spaces Coated with Biofloat Environmentally Friendly Corrosion Inhibitor
- Patented Heavy Duty Roll Form, HSLA Steel Deck Construction with 20,000 psf Concentrated Load Capacity

Available Poseidon Accessories:

- Spud Pockets
- Spuds, 18" diameter x 1/2" wall thickness, in a wide range of lengths from 20ft to 80ft
- Double Drum Hydraulic Winch Systems
- Deck Cleats, Handrail, Safety Ladder
- 8'3" x 7'4" x 4' Rake Sections



POSEIDON® BARGE, LTD

725 East Parr Road, Berne, IN 46711

PH: 866-99-BARGE; FAX: 260-589-2088

WEBSITE: www.poseidonbarge.com

STOCK LOCATIONS: Berne, IN • Plain, WI • Leland, NC
Cocoa, FL • Coeymans, NY • St. Louis, MO • New Orleans, LA