

# POSEIDON® P3 SECTIONAL BARGES



	P3-5-20 Section		P3-5-40 Section	
Length, Overall	20'-11"	6.38 m	41'-7"	12.67 m
Width, Overall	10'-7"	3.23 m	10'-7"	3.23 m
Height, Overall	4' 10-3/4"	1.52 m	4' 10-3/4"	1.52 m
Shipping Weight, Approx.	13,100 lbs	5,942 kg	23,900 lbs	10,841 kg
Draft, Unloaded	12"	0.30 m	11"	0.28 m
Draft, Full Load	30"	0.76 m	30"	0.76 m
Payload at Full Load	9.0 tons	8.2 mT	19.6 tons	17.8 mT



## Standard Features:

- Baril DCC Paint System including Zinc Rich Primer Coat & Premium Abrasion-Resistant Topcoat
- Flush Mounted, Sacrificial Zinc Anodes provide added Corrosion Protection
- Internal Void Spaces Coated with Biofloat Environmentally Friendly Corrosion Inhibitor
- Patented Heavy Duty Roll Form, HSLA Steel Deck Construction with 20,000 psf Concentrated Load Capacity
- The high strength to weight ratio allows two 40ft barges to be shipped per truck, saving freight costs!

## Available Poseidon Accessories:

- Spud Pockets
- Spuds, 18" diameter x 1/2" wall thickness, in a wide range of lengths from 20ft to 80ft
- Double Drum Hydraulic Winch Systems
- Handrail



## POSEIDON® BARGE, LTD

725 East Parr Road, Berne, IN 46711

PH: 866-99-BARGE; FAX: 260-589-2088

WEBSITE: [www.poseidonbarge.com](http://www.poseidonbarge.com)

STOCK LOCATIONS: Berne, IN • Plain, WI • Leland, NC  
Cocoa, FL • Coeymans, NY • St. Louis, MO • New Orleans, LA